

System Specifications

TTR-180 (7")

TTR-250 (10")

TTR-330 (13")

| | | | |
|---|--------------------|--------------------|--------------------|
| Maximum Stock Width | 7" (178mm) | 10" (250mm) | 13" (330mm) |
| Maximum Unwind | 30" (760mm) | 30" (760mm) | 30" (760mm) |
| Maximum Rewind | 30" (760mm) | 30" (760mm) | 30" (760mm) |
| Core size | 3" | 3" | 3" |
| Roll direction | Single | Single | Single |
| Counter | Up | Up | Up |
| Counts in | 10" increments | 10" increments | 10" increments |
| Table top size | Large 30" X 72" | Large 30" X 72" | Large 30" X 72" |
| Maximum roll weight (over 40 lbs recommended) | 45 LBS | 60 LBS | 80 LBS |
| Maximum Speed | 300 FPM | 300 FPM | 300 FPM |
| Power | 110 or 220VAC 60HZ | 110 or 220VAC 60HZ | 110 or 220VAC 60HZ |
| Air | 80 PSI (2.4 atm) | 80 PSI (2.4 atm) | 80 PSI (2.4 atm) |

Options:

Roll lift

8" waste rewind maximum

Dual rewind 16" rewind max

Splicing table

Razor blade slitting attachment

Label counter

Strobe light

Winding both directions

1" Dia Core adapters (each)

1.5" Dia Core adapters (each)

2" Dia Core adapters (each)

Missing labels detecting system (avail. w/label counter only)

Unwind tension control

Roll mapping (avail. w/label counter only)

Wheels - set of four

Over head light kit